

The `xtab` package*

Author: Peter Wilson, Herries Press

Maintainer: Will Robertson

will dot robertson at latex-project dot org

2011/07/31

Abstract

The `xtab` package enables long tables to be automatically broken at page boundaries. It is an extension of the `supertabular` package and also reduces or eliminates some of its weaknesses.

Contents

1	Introduction	1
2	The <code>xtab</code> package	2
2.1	Options	7
3	The implementation	7

List of Tables

1	The principal <code>xtab</code> package commands	2
---	--	---

1 Introduction

Although the `xtab` package was originally developed as part of a suite for typesetting ISO international standards [Wil96], it is also applicable for use with the `LATEX` standard classes. The package is an extension of the `supertabular` package developed by Johannes Braams and Theo Jurriens.¹ It reduces some of the weaknesses noted in the `supertabular` documentation and provides additional functionality.

Section 2 provides the user manual for the package which enables long tables to be automatically broken across multiple pages. Section 3 describes the implementation.

*This file (`xtab.dtx`) has version number v2.3f, last revised 2011/07/31.

¹`supertabular.sty`, version 4.1c, 7 November 1997.

This manual is typeset according to the conventions of the L^AT_EX DOC-STRIP utility which enables the automatic extraction of the L^AT_EX macro source files [GMS94].

2 The xtab package

The `supertabular` package provides for the automatic breaking of a long table across page boundaries. The extension provided here enables the heading on the table on the last page to differ from those on earlier pages of the table. The downside of the extension is that L^AT_EX has to be run twice if the document contains a `supertabular`. However, L^AT_EX is usually run at least twice for any but the simplest document in order to get cross-references and Table of Contents, etc., resolved correctly.

The current version of the extension also either cures or reduces following weaknesses in the `supertabular` package.²

1. Sometimes the top caption of a `supertabular` is printed on one page and the body is printed on the following page(s). That is, there is a lonely caption.
2. Sometimes the last page of a `supertabular` consists of an empty table. That is, just the head and foot of the table are printed.
3. If the number of lines in the first header for the table differs from the number of lines in subsequent headers, then the continuation pages of the table may be too short or, more troubling, too long.

The weaknesses are caused by trying to guess where T_EX will put a page break. The package has to guesstimate how long the next entry will be in the table and, if it is too long for the available space, it puts in its own page break. If its guess is off too much in one direction, T_EX will break the page unexpectedly; if it's off in the other direction `supertabular` will put in an unnecessary page break.

The `xtab` package has reduced, but perhaps not entirely eliminated, these weaknesses. Some hand tuning may still be required.

The principal commands available are given in Table 1.

Table 1: The principal xtab package commands

Command	Effect
<code>\begin{xtabular}{...}</code>	This is equivalent to the normal <code>\begin{tabular}{...}</code> environment. You supply the specification of the columns just as for the normal tabular environment.
Continued on next page	

²I have corresponded with the authors of `supertabular` about these.

Table 1 – continued from previous page

Command	Effect
	<p>All commands that can be used within a <code>tabular</code> environment can also be used within the <code>xtabular</code> environment. Unlike the <code>tabular</code> environment which prevents page breaking within the tabular, the <code>xtabular</code> allows page breaking, so that tabulars can extend automatically across several pages. <code>xtabular</code> starts off with a <code>tabular</code> environment and checks the amount of space left on the page as it adds each row to the tabulation. If the space left on the page is too short for another row, then it ends the current <code>tabular</code>, performs a page break and starts another <code>tabular</code> on the following page. This process is repeated until all the rows have been output. There are special commands for captioning an <code>xtabular</code> as a table, and also elements can be automatically inserted after each (internal) <code>\begin{tabular}</code> and immediately before each <code>\end{tabular}</code>. Do not put a <code>xtabular</code> in a <code>table</code> environment, as the <code>table</code> environment keeps its contents on a single page (presumably you are using <code>xtabular</code> because its contents are longer than one page).</p>
<code>\end{xtabular}</code>	End the <code>xtabular</code> environment.
<code>\begin{mpxtabular}</code>	<p>Like the <code>xtabular</code> environment except that each ‘page’ is put into a <code>minipage</code> first. Thus it is possible to have footnotes inside an <code>mpxtabular</code>. The footnote text is printed at the end of each page.</p>
Continued on next page	

Table 1 – continued from previous page

Command	Effect
<code>\end{mpxtabular}</code>	End the <code>mpxtabular</code> environment.
<code>\topcaption{...}</code>	Note: If any of the following commands are used, then they should be placed before the particular <code>xtabular</code> environment that they apply to. A command to provide a caption for the table. The caption is placed at the top of the table.
<code>\bottomcaption{...}</code>	A command to provide a caption for the table. The caption is placed at the bottom of the table.
<code>\tablecaption{...}</code>	A command to provide a caption for the table. The caption is placed at the default position, which is at the top of the table. Notes: You cannot use the <code>\caption</code> command but you can put a label after any of these captioning commands. If you want captioning, the command must be specified before the start of the supertabular environment. The <code>\...caption{}</code> command(s) remain in effect until changed by another <code>\...caption</code> command.
<code>\tablefirsthead{...}</code>	Defines the contents of the first occurrence of the tabular head. The tabular head is some special treatment of the first row in the table. This command is optional. If used, the header must be closed by the end of line command for tabulars (e.g., <code>\</code>).
<code>\tablehead{...}</code>	Defines the contents of the table head on subsequent pages. For example, you might want to note that this is a continuation of the table on the previous page, as well as repeating any column headings that were given at the start of the <code>xtabular</code> by <code>\tablefirsthead</code> .
Continued on next page	

Table 1 – concluded from previous page

Command	Effect
<code>\tablelasthead{...}</code>	The header must be closed like the <code>\tablefirsthead</code> command. Defines the contents of the table head on the last page of the table. For example, you might want to note that the table is concluded on this page.
<code>\notablelasthead</code>	The header must be closed like the <code>\tablefirsthead</code> command. Switches off the last <code>\tablelasthead</code> . A <code>\tablelasthead</code> stays in effect until overwritten by a new <code>\tablelasthead</code> or cancelled by this command.
<code>\tabletail{...}</code>	The contents of this command are inserted before the (internal) <code>\end{tabular}</code> on each page except for the last page of the table. For example, you might want to note that the table is continued on the next page.
<code>\tablelasttail{...}</code>	The contents of this command are inserted before the final (internal) <code>\end{tabular}</code> of the table. For example, you might want to note that this is where the table ends.

As well as the `xtabular` and `mpxtableular` environments there are the corresponding starred versions (i.e., `xtabular*` and `mpxtableular*` for use in two column mode where the table is meant to span both columns.

Table 1 was produced by code similar to the following:

```

\topcaption{The principal xtab package commands} \label{tab:xtab}
\tablefirsthead{\hline \multicolumn{1}{|c|}{\textbf{Command}} &
\multicolumn{1}{c|}{\textbf{Effect}} \\\hline }
\tablehead{\multicolumn{2}{c}%
{\captionsize\bfseries \tablename\ \thetable{} --
continued from previous page}} \\\
\hline \multicolumn{1}{|c|}{\textbf{Command}} &
\multicolumn{1}{c|}{\textbf{Effect}} \\\hline }
\tablelasthead{\multicolumn{2}{c}%
{\captionsize\bfseries \tablename\ \thetable{} --
concluded from previous page}} \\\
\hline \multicolumn{1}{|c|}{\textbf{Command}} &
\multicolumn{1}{c|}{\textbf{Effect}} \\\hline }
\tabletail{\hline \multicolumn{2}{|r|}{Continued on next page}} \\\hline}
\tablelasttail{\hline \hline}

\begin{center}

```

```

\begin{xtabular}[|l|p{0.5\textwidth}|]
\verb|\begin{xtabular}{...}| & This is equivalent to the normal
\verb|\begin{tabular}{...}| environment.
You supply the specification of the columns
just as for the normal \Lenv{tabular} environment.

\\
&

All commands that can be used within a \Lenv{tabular}
environment can also be used within
the \Lenv{xtabular} environment.

\\
&

Unlike the \Lenv{tabular} environment which prevents page breaking
within the tabular, the \Lenv{xtabular} allows page breaking, so that
tabulars can extend automatically across several pages.
... ..
\verb|\tablelasttail{...}| & The contents of this command are inserted before
the final (internal) \verb|\end{tabular}| of the table.

\\
&

For example, you might want to note that this is where
the table ends.
\\
\end{xtabular}
\end{center}

```

The table is only broken between rows — a row will not be split across pages. This can lead to some bad page breaks, especially if there are rows with a large vertical height (like some in Table 1). It is best to keep rows not too tall.

Unlike the `table` environment which floats, an `xtabular` environment is typeset at the point in the document where the environment is specified. It is best not to start an `xtabular` too close to the bottom of a page otherwise there might be an ugly page break.

`\shrinkheight` The command `\shrinkheight{⟨length⟩}` may be used after the first `\\` in the table to modify the allowed height of the table on that page. A positive `⟨length⟩` decreases the allowed space on the page and a negative `⟨length⟩` increases the allowed space.

For example:

`\shrinkheight{2\baselineskip}` decreases the space per page by two lines.

`\shrinkheight{-\baselineskip}` increases the space per page by one line.

Note that I have never tried using this command so I cannot comment on its efficacy. Instead, I use the `\xentrystretch` command when necessary.

`\xentrystretch` The command `\xentrystretch{⟨decimal-fraction⟩}` can be used before a table to modify the amount of vertical space apparently consumed by each entry in the subsequent table(s). The default is `\xentrystretch{0.1}` which specifies a 10% overestimate in the vertical space. Similarly, `\xentrystretch{0.25}` will overestimate the space by 25%. A different value may be used for each table in

order to eliminate, or at least reduce, bad page breaks. Increasing the value causes fewer entries to be put on a page, thus reducing the chance of \TeX putting in a page break before the `xtab` package is prepared for one.

You may specify the font used for the `\tablehead` and `\tablelasthead` yourself.

Note: Within ISO documents, captions shall be in bold font. The `iso` class also provides a command for setting the size of the font used in captions, namely `\captionsize`. The default value for this is set by the `iso` class. For the curious, the default definition is:

```
\newcommand{\captionsize}{\normalsize}
```

2.1 Options

The `xtab` package has three options which control the amount of information that is written to the `.log` file. The options are:

1. The option `errorshow` (the default) does not write any extra information;
2. The option `pageshow` writes information about when and why `xtab` decides to produce a new page;
3. The option `debugshow`, which also includes `pageshow`, additionally writes information about each line that is added to the table.

Under normal circumstances `xtab` is used without invoking any option. The `pageshow` option may be useful when attempting to cure a bad page break. The `debugshow` option, as its name implies, is principally of use to the `xtab` developer.

Independently of the options, the command `\sstraceon` may be used at any point in the document to turn on printing of `debugshow` data. This can be turned off later by the `\sstraceoff` command, which will stop all `...show` printing.

3 The implementation

The `xtab` package provides an extension to the `supertabular` package written by Johannes Braams and Theo Jurriens.³ The major portion of the following documentation is taken from `supertabular.dtx`. The package is designed to be used with the `iso` class in addition to the usual `article`, etc., classes.

The extension provided here enables the heading on the table on the last page to differ from those on earlier pages of the table. The implementation of the extension is based on ideas in David Carlisle's `longtable` package. The downside of the extension is that \LaTeX has to be run twice if the document contains a `supertabular`. However, \LaTeX is usually run at least twice for any but the simplest document in order to get cross-references and Table of Contents, etc., resolved correctly.

³`supertabular.sty`, version 4.1c, 7 November 1997.

The current version of the extension also either cures or reduces following weaknesses in the `supertabular` package.⁴

1. Sometimes the top caption of a `supertabular` is printed on one page and the body is printed on the following page(s). That is, there is a lonely caption.
2. Sometimes the last page of a `supertabular` consists of an empty table. That is, just the head and foot of the table are printed.
3. If the number of lines in the first header for the table differs from the number of lines in subsequent headers, then the continuation pages of the table may be too short or, more troubling, too long.

The first version of `xtab` imported much of the code from the `supertabular` package (version 3.7) but I found that this did not work well because there were incompatible coded versions of `supertabular` available on CTAN. Further, I found that there were some problems with the original `supertabular` code in any case.⁵ I have to make the assumption that other users may have dissimilar or problematic versions, so include all the code here, and thus any errors can now be laid at my door.

The requirement for compatibility with the `iso` class is achieved by modifications to the `\ST@caption` command only. Effectively this is orthogonal to the code required to implement the extension.

Now for the code itself. As syntactic sugar, all new macros for the extension have the prefix ‘PWST’ to distinguish them from the original macros. I have also denoted all extensions to the original `supertabular` by introducing them as *Extension*.

Announce the name and version of the package, which requires L^AT_EX 2_ε.

```
1 <*xtab>
```

`\c@tracingst` There are three options with the package which control the amount of information written to the log file:

1. `errorshow` (the default) no extra information
2. `pageshow` writes information about page breaking
3. `debugshow` adds information about each line that is added to the tabular

```
2 \newcount\c@tracingst
```

```
3 \DeclareOption{errorshow}{\c@tracingst\z@}
```

Extension: The next line in the original code did not do what the authors intended; the number should have been 3 rather than 2.

```
4 %%%\DeclareOption{pageshow}{\c@tracingst\tw@}
```

```
5 \DeclareOption{pageshow}{\c@tracingst\thr@@}
```

```
6 \DeclareOption{debugshow}{\c@tracingst5\relax}
```

```
7 \ProcessOptions
```

⁴Only the first two of these have been recognised by the authors of `supertabular`.

⁵I also found a bug in the 4.1b version which the authors kindly fixed in version 4.1c.

`\if@topcaption` The user-commands `\topcaption` and `\bottomcaption` set the flag `@topcaption` to determine where to put the tablecaption. The default is to put the caption on the top of the table

```

8 \newif\if@topcaption \@topcaptiontrue
9 \def\topcaption{\@topcaptiontrue\tablecaption}
10 \def\bottomcaption{\@topcaptionfalse\tablecaption}

```

`\PWST@thecaption` *Extension:* `\PWST@thecaption` is used to store the text of the table's caption. The vertical space required by a caption is stored in `\PWSTcapht`.

```

11 \gdef\PWST@thecaption{}
12 \newdimen\PWSTcapht

```

`\tablecaption` This command has to function exactly like `\caption` does except it has to store its argument (and the optional argument) for later processing *within* the supertabular environment.

```

13 \long\def\tablecaption{%
14   \refstepcounter{table}\@dblarg{\@xtablecaption}}
15 \long\def\@xtablecaption[#1]#2{%

```

Extension: I store the caption text for later measurement.

```

16   \long\gdef\PWST@thecaption{#2}%

```

Finish up with the original code.

```

17   \long\gdef\@process@tablecaption{\ST@caption{table}[#1]{#2}}
18   \global\let\@process@tablecaption\relax

```

`\ifST@star` This switch is used in the internal macros to remember which kind of environment was started.

```

19 \newif\ifST@star

```

`\ifST@mp` This flag is used in the internal macros to remember if the tabular is to be put in a minipage.

```

20 \newif\ifST@mp

```

`\ST@wd` For the `supertabular*` environment it is necessary to store the intended width of the tabular.

```

21 \newdimen\ST@wd

```

`\ST@rightskip` For the `mpsupertabular` environments we need special versions of `\leftskip`, `\ST@leftskip` `\rightskip` and `\parfillskip`.

```

22 \newskip\ST@rightskip
23 \newskip\ST@leftskip
24 \newskip\ST@parfillskip

```

`\@initisotab` Required for ISO class, and check if class loaded.

```

25 \@ifundefined{@initisotab}{%
26   \newcommand{\@initisotab}{}%
27   \newif\ifinfloat{\typeout{xtab using iso captions}}

```

`\ST@caption` This is a redefinition of LaTeX's `\@caption`, `\@makecaption` is called within a group so as not to return to `\normalsize` globally. In the original a fix was made for the 'feature' of the `\@makecaption` of `article.sty` and friends that a caption *always* gets a `\vskip 10pt` at the top and *none* at the bottom; if a user wants to precede his table with a caption this results in a collision. This fix is not implemented here as I think it should be done by the user modifying `\beforecaptionskip` and `\aftercaptionskip`.

Extension: The ISO captioning is also initialised.

```

28 \long\def\ST@caption#1[#2]#3{\par%
29   \@initisotab
30   \addcontentsline{\csname ext@#1\endcsname}{#1}%
31     {\protect\numberline{%
32       \csname the#1\endcsname}{\ignorespaces #2}}%
33   \begingroup
34     \@parboxrestore
35     \normalsize
36     %% \if@topcaption \vskip -10\p@ \fi
37     \@makecaption{\csname fnum@#1\endcsname}{\ignorespaces #3}\par
38     %% \if@topcaption \vskip 10\p@ \fi
39   \endgroup

```

Extension: The height of the caption is subtracted from the available space on the page.

```

40 \global\advance\ST@pageleft -\PWSTcapht
41 \ST@trace\tw@{Added caption. Space left for xtabular: \the\ST@pageleft}}

```

`\tablehead` `\tablehead` activates the new tabular `\cr` commands.

```

\tablefirsthead 42 \newcommand\tablehead[1]{%
43   \gdef\@tablehead{%
44     \noalign{%
45       \global\let\@savcr=\%
46       \global\let\@=\org@tabularcr}%
47     #1%
48     \noalign{\global\let\@=\@savcr}}
49 \tablehead{}
50 \newcommand\tablefirsthead[1]{\gdef\@table@first@head{#1}}

```

`\c@PWSTtable` *Extension:* These are counters for the supertabular extension. `c@PWSTtable`
`\PWSTlastpage` counts the number of supertabulars in case one or more are not captioned. `PW-`
`\PWSTcurpage` `STlastpage` is a counter holding the number of pages that a supertabular uses and
`\PWSTpenultimate` `PWSTpenultimate` is the penultimate page. `PWSTcurpage` counts the current num-
`\PWSTtempc` ber of supertabular pages processed. `PWSTtempc` is a scratch counter for page
`\PWSTlines` processing.
`\PWSThead` 51 \newcounter{PWSTtable}
`\PWSTlasthead` 52 \newcount\PWSTlastpage
53 \newcount\PWSTpenultimate
54 \newcount\PWSTcurpage
55 \newcount\PWSTtempc

Extension: `PWSTlines` is used to count the number of supertabular entry lines on a page. Estimates of the number of lines in the normal table heading is held by `PWSThead`, and similarly `PWSTlasthead` is for the number of lines in the last heading.

```
56 \newcount\PWSTlines
57 %% \newcount\PWSThead
58 %% \newcount\PWSTlasthead
```

`\iffirstcall` *Extension:* This is used by the extension code to flag if the presumed last page overflows. If overflow occurs, then `firstcall` is set to false.

```
59 \newif\iffirstcall
```

`\PWST@lastht` *Extension:* The estimated height of a table header and tail (i.e., the height of an empty table) for the last page of a supertabular is stored in `\PWSTlastht`. Similarly, the corresponding height of an empty table on a general page (neither the first nor the last) is stored in `\PWSTgeneralht`. `\PWST@ht` is a scratch variable.

```
\PWST@generalht
\PWST@ht
```

```
60 \newdimen\PWST@lastht
61 \newdimen\PWST@generalht
62 \newdimen\PWST@ht
```

`\tablelasthead` *Extension:* `\tablelasthead` is the extension user command to specify the heading for the last page of a supertabular. The command `\notablelasthead` switches off the last heading. This has to be used if a last headed table precedes one that does not have a special last head.

```
\@table@last@head
\notablelasthead
```

```
63 \newcommand{\tablelasthead}[1]{\gdef\@table@last@head{#1}}
64 \newcommand{\notablelasthead}{\let\@table@last@head\relax}
```

Now initialize these commands.

```
65 \tablelasthead{}
66 \notablelasthead
```

`\tabletail` `\tablelasttail` `\tabletail` is the user command to specify the appearance of the bottom of each tabular on a page. Special treatment is given to the end of the supertabular via the `\tablelasttail` command.

If the user uses an extra amount of tabular-data (like `\multicolumn`) in `\tabletail` T_EX starts looping because of the definition of `\nextline`. So make `\` act like just a `\cr` inside this tail to prevent the loop. Save and restore the value of `\`

```
67 \newcommand\tabletail[1]{%
68 \gdef\@tabletail{%
69 \noalign{%
70 \global\let\@savcr=\%
71 \global\let\=\org@tabularcr}%
72 #1%
73 \noalign{\global\let\=\@savcr}}
74 \tabletail{}
75 \newcommand\tablelasttail[1]{\gdef\@table@last@tail{#1}}
76 \tablelasttail{}
```

`\sttraceon` The original supertabular included a tracing mechanism to follow the decisions
`\sttraceoff` supertabular made about page breaking. This is now also used as a debugging
mechanism for the extension.

```
77 \newcommand\sttraceon{\c@tracingst5\relax}
78 \newcommand\sttraceoff{\c@tracingst\z@}
```

`\ST@trace` A macro that gets the trace message as its argument

```
79 \newcommand\ST@trace[2]{%
80 \ifnum\c@tracingst>#1\relax
81 \GenericWarning{(x\tab)\@spaces\@spaces}{Package x\tab: #2}%
82 \fi}
```

`\ST@pageleft` This register holds the estimate of the amount of space left over on the current
page. This is used in the decision when to start a new page.

```
83 \newdimen\ST@pageleft
```

`\shrinkheight` `\shrinkheight` is a command to diminish the value of `\ST@pageleft` if necessary.
`\setSTheight` `\setSTheight` sets the value of `\ST@pageleft` if necessary.

```
84 \newcommand*\shrinkheight[1]{%
85 \noalign{\global\advance\ST@pageleft-#1\relax}}
86 \newcommand*\setSTheight[1]{%
87 \noalign{\global\ST@pageleft=#1\relax}}
```

`\xentrystretch` *Extension:* Provide a user and internal command for fudging the estimated space
`\PWST\xentrystretch` taken by a table entry. Initialise to 10% increase.

```
88 \newcommand{\xentrystretch}[1]{\def\PWST\xentrystretch{#1}}
89 \xentrystretch{0.1}
```

`\ST@headht` The register `\ST@headht` holds the height of the first head of a supertabular.
`\ST@tailht` The register `\ST@tailht` holds the height of the tail.

```
90 \newdimen\ST@headht
91 \newdimen\ST@tailht
```

`\ST@pagesofar` Register `\ST@pagesofar` stores the estimate of the amount of the page already
filled up.

```
92 \newdimen\ST@pagesofar
```

`\ST@pboxht` The measured (total) height of a parbox argument.

```
93 \newdimen\ST@pboxht
```

`\ST@lineht` The estimated height of a normal line is stored in `\ST@lineht`. The register
`\ST@stretchht` `\ST@stretchht` is used to store the difference between the normal line height and
`\ST@prevht` the line height when `\arraystretch` has a non-standard value. This is used in the
case when p-box entries are added to the tabular. `\ST@prevht` stores the height
of the previous line to use it as an estimate for the height of the next line. This is
needed for a better estimate of when to break the tabular.

```
94 \newdimen\ST@lineht
95 \newdimen\ST@stretchht
96 \newdimen\ST@prevht
```

`\ST@toadd` When a tabular row is ended with `\\[...]` we need to temporarily store the optional argument in `\ST@toadd`.

```

97 \newdimen\ST@toadd

```

`\ST@dimen` A private scratch dimension register.

```

98 \newdimen\ST@dimen

```

`\ST@pbox` A box register to store the contents of a parbox.

```

99 \newbox\ST@pbox
100

```

`\ST@tabularcr` These are redefinitions of `\@tabularcr` and `\@xtabularcr`. This is needed to include `\ST@cr` in the definition of `\@xtabularcr`.

`\ST@xtabularcr`

`\ST@argtabularcr` All redefined macros have names that are similar to the original names, except with a leading ‘ST’.

```

101 \def\ST@tabularcr{%
102   {\ifnum0=} \fi
103   \@ifstar{\ST@xtabularcr}{\ST@tabularcr}}
104 \def\ST@xtabularcr{%
105   \@ifnextchar[%
106     {\ST@argtabularcr}%
107     {\ifnum0={\fi}\cr\ST@cr}}
108 \def\ST@argtabularcr[#1]{%
109   \ifnum0={\fi}%
110   \setlength\@tempdima{#1}%
111   \ifdim \@tempdima>z@
112     \unskip\ST@xargarraycr{#1}%
113   \else
114     \ST@yargarraycr{#1}%
115   \fi}

```

`\ST@xargarraycr` In this case we need to copy the value of the optional argument of `\\` in our private register `\ST@toadd`.

```

116 \def\ST@xargarraycr#1{%
117   \setlength\@tempdima{#1}%
118   \advance\@tempdima \dp \@arstrutbox
119   \vrule \@height\z@ \@depth\@tempdima \@width\z@ \cr
120   \noalign{\setlength{\global\ST@toadd}{#1}}\ST@cr
121 }

```

Here we need to insert `\ST@cr`

```

122 \def\ST@yargarraycr#1{%
123   \cr\noalign{%
124     \setlength{\global\ST@toadd}{#1}%
125     \vskip\ST@toadd
126   }\ST@cr
127 }

```

`\ST@startpbox` The macros that deal with parbox columns need to be redefined, because we need to know the size of the parbox.

```

128 \def\ST@startpbox#1{%
    To achieve our goal we need to save the text in box.
129 %%% \setbox\ST@pbox\vtop\bgroup\hsize#1\@arrayparboxrestore}
130 \setbox\ST@pbox\vtop\bgroup\setlength\hsize{#1}\@arrayparboxrestore}

```

`\ST@astartpbox` supertabular version of `\@astartpbox`.

```

131 \def\ST@astartpbox#1{%
132 \bgroup\setlength\hsize{#1}%
133 %%% \setbox\ST@pbox\vtop\bgroup\hsize#1\@arrayparboxrestore}
134 \setbox\ST@pbox\vtop\bgroup\setlength\hsize{#1}\@arrayparboxrestore}

```

`\ST@endpbox` supertabular versions of `\@endpbox` and `\@aendpbox`.

`\ST@aendpbox`

```

135 \def\ST@endpbox{%
136 \@finalstrut\@arstrutbox\par\egroup
137 \ST@dimen=\ht\ST@pbox
138 \advance\ST@dimen by \dp\ST@pbox
139 \ifnum\ST@pboxht<\ST@dimen
140 \global\ST@pboxht=\ST@dimen
141 \fi
142 \ST@dimen=\z@
143 \box\ST@pbox\hfil}
144 \def\ST@aendpbox{%
145 \@finalstrut\@arstrutbox\par\egroup
146 \ST@dimen=\ht\ST@pbox
147 \advance\ST@dimen by \dp\ST@pbox
148 \ifnum\ST@pboxht<\ST@dimen
149 \global\ST@pboxht=\ST@dimen
150 \fi
151 \ST@dimen=\z@
152 \unvbox\ST@pbox\egroup\hfil}

```

`\estimate@lineht` Estimates the height of normal line taking `\arraystretch` into account. Also computes the difference between a ‘normal’ line and a stretched one.

```

153 \def\estimate@lineht{%
154 \ST@lineht=\arraystretch \baselineskip
155 \global\advance\ST@lineht by 1\p@
156 \ST@stretchht\ST@lineht\advance\ST@stretchht-\baselineskip
157 \ifdim\ST@stretchht<\z@\ST@stretchht\z@\fi
158 \ST@trace\tw@{Basic line height: \the\ST@lineht\MessageBreak%
159 \quad Arrayed line height: \the\ST@stretchht}%
160 \global\advance\ST@lineht \PWST@xentrystretch\ST@lineht
161 \ST@trace\tw@{Stretched line height: \the\ST@lineht}}

```

`\@calfirstpageht` Estimates the space left on the current page and decides whether the tabular can be started on this page or on a new page. Aspects of the original code are modified for the extension.

```

162 \def\@calfirstpageht{%
163   \ST@trace\tw@{Calculating height of xtabular on first page}%

```

The \TeX register `\pagetotal` contains the height of the page so far, the \LaTeX register `\@colroom` contains the height of the column.

```

164   \global\ST@pagesofar\pagetotal
165   \global\ST@pageleft\@colroom
166   \ST@trace\tw@{Height of previous text = \the\pagetotal; \MessageBreak
167     Height of column = \the\ST@pageleft}%

```

When we are in twocolumn mode \TeX may still be collecting material for the first column although there seems to be no space left. In this case we have to check against two times `\ST@pageleft`.

```

168   \if@twocolumn
169     \ST@trace\tw@{two column mode}%
170     \if@firstcolumn
171       \ST@trace\tw@{First column}%
172       \ifnum\ST@pagesofar > \ST@pageleft
173         \global\ST@pageleft=2\ST@pageleft
174         \ifnum\ST@pagesofar > \ST@pageleft
175           \newpage\@calnextpageht
176           \ST@trace\tw@{starting new page}%
177         \else

```

In this case we're in the second column, so we have to compensate for the material in the first column.

```

178           \ST@trace\tw@{Second column}%
179           \global\advance\ST@pageleft -\ST@pagesofar
180           \global\advance\ST@pageleft -\@colroom
181         \fi

```

When `\ST@pagesofar` is smaller than `\ST@pageleft` \TeX is still collecting material for the first column, so we can start a new tabular environment like we do on a single column page.

```

182     \else
183       \global\advance\ST@pageleft by -\ST@pagesofar
184       \global\ST@pagesofar\z@
185     \fi
186   \else

```

When we end up here, \TeX has already decided it had enough material for the first column and is building the second column.

```

187     \ST@trace\tw@{Second column}%
188     \ifnum\ST@pagesofar > \ST@pageleft
189       \ST@trace\tw@{starting new page}%
190       \newpage\@calnextpageht
191     \else
192       \global\advance\ST@pageleft by -\ST@pagesofar
193       \global\ST@pagesofar\z@
194     \fi
195   \fi
196 \else

```

In one column mode there is a simple decision.

```

197     \ST@trace\tw@{one column mode}%
198     \ifnum\ST@pagesofar > \ST@pageleft
199         \ST@trace\tw@{starting new page}%
200         \newpage\@calnextpageht

```

When we are not starting a new page subtract the size of the material already on it from the available space.

```

201     \else
202         \global\advance\ST@pageleft by -\ST@pagesofar
203         \global\ST@pagesofar\z@
204     \fi
205 \fi
206 \ST@trace\tw@{Available height: \the\ST@pageleft}%

```

Now we need to know the height of the head of the table. In order to measure this we typeset it in a normal tabular environment.

```

207 \ifx\@tablehead\@empty
208     \ST@headht=\z@
209 \else
210     \setbox\@tempboxa=\vbox{\@arrayparboxrestore
211         \ST@restore
212         \expandafter\tabular\expandafter{\ST@tableformat}%
213         \@tablehead\endtabular}%
214     \ST@headht=\ht\@tempboxa\advance\ST@headht\dp\@tempboxa
215 \fi
216 \ST@trace\tw@{Height of head: \the\ST@headht}%

```

To decide when to start a new page, we need to know the vertical size of the tail of the table.

```

217 \ifx\@tabletail\@empty
218     \ST@tailht=\z@
219 \else
220     \setbox\@tempboxa=\vbox{\@arrayparboxrestore
221         \ST@restore
222         \expandafter\tabular\expandafter{\ST@tableformat}%
223         \@tabletail\endtabular}%
224     \ST@tailht=\ht\@tempboxa\advance\ST@tailht\dp\@tempboxa
225 \fi

```

We add the average height of a line to this because when we decide to continue the tabular we need to have enough space left for one line and the tail.

```

226 \advance\ST@tailht by \ST@lineht
227 \ST@trace\tw@{Height of tail: \the\ST@tailht}%
228 \ST@trace\tw@{Maximum space for xtabular: \the\ST@pageleft}%

```

Now we decide whether we can continue on the current page or whether we need to start a new page. We assume that the minimum height of a tabular is the height of the head and tail and one line of data. If that doesn't fit, start a new page.


```

229 \@tempdima\ST@headht
230 \advance\@tempdima\ST@lineht
231 \advance\@tempdima\ST@tailht

```

Extension: I also add the height of the caption to the required space. The amount to be added depends on whether it is a top or bottom caption. Allowance is also made for skips around the caption.

```

232 \if@topcaption
233   \setbox\@tempboxa=\vbox{\PWST@thecaption}%
234   \PWSTcapht=\ht\@tempboxa\advance\PWSTcapht\dp\@tempboxa
235   \advance\PWSTcapht by 20\p@
236 \else
237   \PWSTcapht = 10\p@
238 \fi
239 \ST@trace\tw@{Caption height: \the\PWSTcapht}%
240 \advance\@tempdima\PWSTcapht

```

Continue with the original code.

```

241 \ST@trace\tw@{Minimum height of xtabular: \the\@tempdima}%
242 \ifnum\@tempdima>\ST@pageleft
243   \ST@trace\tw@{starting new page}%

```

Extension: The next line in the original code is `\newpage\@calnextpageht`. I need to start a new page, making allowance for the space required by the caption.

```

244   \newpage
245   \global\ST@pageleft\@colroom
246   \global\advance\ST@pageleft by -\PWSTcapht
247   \global\ST@pagesofar=\z@

```

Finish up with the original code.

```

248 \fi} % end \@calfirstpageheight
249

```

`\@calnextpageht` This calculates the maximum height of the tabular on all subsequent pages of the supertabular environment.

```

250 \def\@calnextpageht{%
251   \ST@trace\tw@{Calculating height of xtabular on next page}%
252   \global\ST@pageleft\@colroom
253   \global\ST@pagesofar=\z@
254   \ST@trace\tw@{Maximum space for xtabular: \the\ST@pageleft}}

```

`\PWSTcalchtlines` *Extension:* A macro to calculate the space required by an empty table and the number of lines in an empty table.

The appropriate heads and tails are typeset in a temporary box so we can measure them.

```

255 \newcommand{\PWSTcalchtlines}{%
  Measure the lasttail.
256 \setbox\@tempboxa=\vbox{\@arrayparboxrestore
257   \ST@restore
258   \expandafter\xtabular\expandafter{\ST@tableformat}%

```

```

259 \table@last@tail\endtabular}%
260 \PWST@ht=\ht\@tempboxa\advance\PWST@ht\dp\@tempboxa
261 \global\PWST@lastht = \PWST@ht

And repeat for the lasthead.

262 \setbox\@tempboxa=\vbox{\@arrayparboxrestore
263 \ST@restore
264 \expandafter\tabular\expandafter{\ST@tableformat}%
265 \table@last@head\endtabular}%
266 \PWST@ht = \ht\@tempboxa\advance\PWST@ht\dp\@tempboxa
267 \global\advance\PWST@lastht by \PWST@ht
268 \ST@trace\tw@{Height of empty xtabular on last page = \the\PWST@lastht}%

```

Now repeat pretty well all of the above for a general table (i.e., one that is not on the first page nor the designated last page).

First the tail.

```

269 \setbox\@tempboxa=\vbox{\@arrayparboxrestore
270 \ST@restore
271 \expandafter\tabular\expandafter{\ST@tableformat}%
272 \tabletail\endtabular}%
273 \PWST@ht=\ht\@tempboxa\advance\PWST@ht\dp\@tempboxa
274 \global\PWST@generalht = \PWST@ht

```

And on to the general head.

```

275 \setbox\@tempboxa=\vbox{\@arrayparboxrestore
276 \ST@restore
277 \expandafter\tabular\expandafter{\ST@tableformat}%
278 \tablehead\endtabular}%
279 \PWST@ht = \ht\@tempboxa\advance\PWST@ht\dp\@tempboxa
280 \global\advance\PWST@generalht by \PWST@ht}

```

`\PWSTcalnextpageht` *Extension:* From some experiments that I ran it appeared as though the supertabular package ignored the possibility that the space required for the table header and tail on pages after the first one might be different. If the subsequent head/tail combination were longer (i.e., took more vertical space) then the table could overflow the page. This is an attempt to fix this problem by calculating the actual minimum space required after the first page.

The calculations are similar to, but simpler, than those for `\@calfirstpageht`.

```

281 \newcommand{\PWSTcalnextpageht}{%
282 \ifnum\PWSTcurpage = \PWSTpenultimate
283 \ST@trace\tw@{Calculating height of xtabular on last page}%

```

We are on the penultimate page, so get the height of the last head/tail.

```

284 \PWST@ht=\PWST@lastht

```

Otherwise I need the general page data.

```

285 \else
286 \ST@trace\tw@{Calculating height of xtabular on next general page}%
287 \PWST@ht=\PWST@generalht
288 \fi

```

Having dealt with the two cases, I can now calculate the minimum space for a supertabular on the following page.

```
289 \global\ST@pageleft\@colroom
290 \global\advance\ST@pageleft -\PWST@ht
291 \global\ST@pagesofar=\z@
292 \ST@trace\tw@{Available space for xtabular: \the\ST@pageleft}}
```

`\x@supertabular` The various supertabular environments share a lot of code. Thus, to avoid needless repetition, the shared code is defined in this macro.

This macro has been modified as part of the supertabular extension.

```
293 \def\x@supertabular{%
```

First save the original definition of `\tabular` and then make it point to `\inner@tabular`. This is done to enable supertabular cells to contain a `tabular` environment without getting unexpected results when the `supertabular` would be split across this inner `tabular` environment.

```
294 \let\org@tabular\tabular
295 \let\tabular\inner@tabular
```

The same has to be done for the `tabular*` environment. The coding is more verbose.

```
296 \expandafter\let
297   \csname org@tabular*\expandafter\endcsname
298   \csname tabular*\endcsname
299 \expandafter\let\csname tabular*\expandafter\endcsname
300   \csname inner@tabular*\endcsname
```

Extension: The original code printed out the top caption at this point. If there is too little space on the first page of the table, the tabular data is printed on the following page. If this is the case (and its not known yet whether it is), then the caption should also be printed on the following page.

```
301 %%% \if@topcaption \@process@tablecaption \fi
```

Back to the original code. Save the original definition of `\%`.

```
302 \global\let\oldcr=\%
```

Save the current value of `\baselineskip`, as we need it in the calculation of the average height of a line.

```
303 \def\baselineskp{\baselineskip}%
```

We have to check whether `array.sty` was loaded, because some of the internal macros have different names.

```
304 \ifx\undefined\@classix
```

Save old `\@tabularcr` and insert the definition of `\@stabularcr`.

```
305 \let\org@tabularcr\@tabularcr
306 \let\@tabularcr\ST@tabularcr
```

Activate the new parbox algorithm.

```
307 \let\org@startpbox=\@startpbox
308 \let\org@endpbox=\@endpbox
```

```

309 \let\@@startpbox=\ST@startpbox
310 \let\@@endpbox=\ST@endpbox
311 \else

```

When `array.sty` was loaded things are a bit different.

```

312 \let\org@tabularcr\@arraycr
313 \let\@arraycr\ST@tabularcr
314 \let\org@startpbox=\@startpbox
315 \let\org@endpbox=\@endpbox
316 \let\@startpbox=\ST@astartpbox
317 \let\@endpbox=\ST@aendpbox
318 \fi

```

Check if the head of the table should be different for the first and subsequent pages.

```

319 \ifx\@table@first@head\undefined
320 \let\@@tablehead=\@tablehead
321 \else
322 \let\@@tablehead=\@table@first@head
323 \fi

```

The first part of a supertabular may be moved to the next page if it doesn't fit on the current page. Subsequent parts can not be moved; therefore we will have to switch the definition of `\ST@skippart` around.

```

324 \let\ST@skippage\ST@skipfirstpart

```

Now we can estimate the average line height and the height of the first page of the supertabular.

```

325 \estimate@lineht
326 \@calfirstpageht

```

Extension: Call the macro to initialize the extension code for this table.

```

327 \PWSTinit

```

Extension: At this point I know, and have adjusted for, the page on which the first part of the table will be printed. It should now be safe to print the top caption, if any. Unfortunately, in spite of everthing, the `TEX` page breaking mechanism might still think that there is too little space left.

```

328 \if@topcaption \@process@tablecaption \fi
329 \noindent

```

Extension: Finally, subtract the space required by the header and the tail (as these don't update the available space when output).

```

330 \global\advance\ST@pageleft -\ST@headht%
331 \ST@trace\tw@{Available space after accounting for header: \the\ST@pageleft}%
332 \global\advance\ST@pageleft -\ST@tailht%
333 \ST@trace\tw@{Available space after accounting for tail: \the\ST@pageleft}}

```

`\PWSTinit` *Extension:* This routine initialises the extension data.

```

334 \newcommand{\PWSTinit}{%

```

At the end of processing each supertabular (see later) the number of pages consumed by the supertabular is written to the .aux file. At the start of a supertabular, after incrementing the number of supertabulars processed, the prior number of pages are read from the file. These are stored in *PWSTlastpage*.

```
335 \global\advance\c@PWSTtable\@ne
336 \global\expandafter\let\expandafter\PWSTtempc
337 \csname PWST@romannumeral\c@PWSTtable\endcsname
```

I have to take account of the fact that there might be no entry in the .aux file, and hence the lastpage number might not be set.

```
338 \ifx\PWSTtempc\relax
339 \ST@trace\tw@{Table \the\c@PWSTtable: Processing for the first time}%
340 \PWSTlastpage=\@m% = 1000
341 \else
342 \PWSTlastpage=\PWSTtempc
343 \fi
344 \ST@trace\tw@{Table \the\c@PWSTtable: last page set to \the\PWSTlastpage}%
```

Set the current page counter to unity.

```
345 \PWSTcurpage=\@ne
```

Perform the calculations for the empty table data.

```
346 \PWSTcalchtlines
```

Initialise the line counter and set `firstcall` to TRUE.

```
347 \global\PWSTlines=\z@
348 \global\firstcalltrue
```

If we have the `iso` class, then I have to flag that we are in a ‘float’.

```
349 \infloattrue}
```

`\xtable` We start by looking for an optional argument, which will be duly ignored as it seems to make no sense to try to align a multipage table in the middle...

Extension: Use `xtable` instead of `supertabular`, and similarly for the others, so this will not be mentioned explicitly again.

```
350 \def\xtable{%
351 \@ifnextchar[{\@supertabular}%]
352 {\@supertabular []}}
```

`\@supertabular` We can now save the preamble of the tabular in a macro.

```
353 \def\@supertabular[#1]#2{%
354 \def\ST@tableformat{#2}%
355 \ST@trace\tw@{Starting a new xtable}%
```

Then remember that this is not a `supertabular*` environment.

```
356 \global\ST@starfalse
```

Don’t use minipages.

```
357 \global\ST@mpfalse
```

Most of the following code is shared between the `supertabular` and `supertabular*` environments. So to avoid duplication it is stored in a macro.

```
358 \x@supertabular
    Finally start a normal tabular environment.
359 \expandafter\org@tabular\expandafter{\ST@tableformat}%
360 \@@tablehead}
```

`\xtabular*` We start by looking for the optional argument of the tabular environment.

```
361 \@namedef{xtabular*}#1{%
362 \@ifnextchar[{\@nameuse{@supertabular*}#{1}}%
363             {\@nameuse{@supertabular*}#{1} []}%]
364 }
```

We start by saving the intended width and the preamble of the `tabular*`.

```
365 \@namedef{@supertabular*}#1[#2]#3{%
366 \ST@trace\tw@{Starting a new xtabular*}%
367 \def\ST@tableformat{#3}%
368 \ST@wd=#1\relax
369 \global\ST@startrue
370 \global\ST@mpfalse
```

Now we can call the common code for both environments.

```
371 \x@supertabular
    And we can start a normal tabular* environment.
372 \expandafter\csname org@tabular*\expandafter\endcsname
373 \expandafter{\expandafter\ST@wd\expandafter}%
374 \expandafter{\ST@tableformat}%
375 \@@tablehead}
```

`\mpxtabular` This version of the `supertabular` environment puts each tabular into a minipage, thus making footnotes possible. We start by looking for an optional argument, which will be ignored as it makes no sense to try and align a multipage table in the middle...

```
376 \def\mpxtabular{%
377 \@ifnextchar[{\@mpsupertabular}%]
378             {\@mpsupertabular []}}
```

We can now save the preamble in a macro.

```
379 \def{@mpsupertabular}#1[#2]#3{%
380 \def\ST@tableformat{#2}%
381 \ST@trace\tw@{Starting a new mpxtabular}%
```

Remember that this is not a `mpsupertabular*` environment and also note we have to close the minipage later.

```
382 \global\ST@starfalse
383 \global\ST@mptrue
```

Since we are about to start a minipage of `\columnwidth` the horizontal alignment will not work. We have to remember the values and then restore them inside the minipage.

```

384 \ST@rightskip \rightskip
385 \ST@leftskip \leftskip
386 \ST@parfillskip \parfillskip

```

Call the code that is common to all the environments.

```

387 \x@supertabular
    Finally, start a normal tabular
388 \minipage{\columnwidth}%
389 \parfillskip\ST@parfillskip
390 \rightskip \ST@rightskip
391 \leftskip \ST@leftskip
392 \noindent\expandafter\org@tabular\expandafter{\ST@tableformat}%
393 \@@tablehead}
394

```

`\mpxtabular*` We start by looking for the optional argument of the tabular environment.

```

395 \@namedef{mpxtabular*}#1{%
396   \@ifnextchar[{\@nameuse{@mpsupertabular*}#1}]%
397   {\@nameuse{@mpsupertabular*}#1}[]}%
398 }

```

Now we can save the intended width and the preamble of the `tabular*`.

```

399 \@namedef{@mpsupertabular*}#1[#2]#3{%
400   \ST@trace\tw@{Starting a new mpxtabular*}%
401   \def\ST@tableformat{#3}%
402   \ST@wd=#1\relax
403   \global\ST@startrue
404   \global\ST@mptrue
405   \ST@rightskip \rightskip
406   \ST@leftskip \leftskip
407   \ST@parfillskip \parfillskip

```

Now is the time to call the common code for both environments.

```

408 \x@supertabular
    And we can start a normal tabular* environment.
409 \minipage{\columnwidth}%
410 \parfillskip\ST@parfillskip
411 \rightskip \ST@rightskip
412 \leftskip \ST@leftskip
413 \noindent\expandafter\csname org@tabular*\expandafter\endcsname
414 \expandafter{\expandafter\ST@wd\expandafter}%
415 \expandafter{\ST@tableformat}%
416 \@@tablehead}

```

`\endxtabular` These close the `xtabular` and `xtabular*` environments.

`\endxtabular*` For the extension, this macro has been modified to write out to the `.aux` file the number of pages used for the `supertabular`.

```

417 \def\endxtabular{%
418   \ifx\@table@last@tail\undefined

```

```

419   \@tabletail
420   \else
421     \@table@last@tail
422   \fi
423   \csname endtabular\ifST@star*\fi\endcsname

```

While studying the original code to determine where additions were needed for the extension, I realized that the last part of the `\end...` code was common to all the environments. I have broken it out into a separate routine which also includes the modification needed for the extension.

```

424   \x@endsupertabular

```

And back to the original code.

```

425   \ST@trace\tw@{Ended a xtabular\ifST@star*\fi}}

```

The definition of the ending of the `xtabular*` environment is simple:

```

426 \expandafter\let\csname endxtabular*\endcsname\endxtabular

```

`\x@endsupertabular` This macro contains the code that is common to all the `\end...` commands. It includes the modification required for the extension.

```

427 \newcommand{\x@endsupertabular}{%

```

Restore the original definition of `\@tabularcr`

```

428   \ST@restore

```

Check if we have to insert a caption and restore to default behaviour of putting captions at the top.

```

429   \if@topcaption
430   \else
431     \@process@tablecaption
432     \global\@topcaptiontrue
433   \fi

```

Restore the meaning of `\\` to the one it had before the start of this environment. Also re-initialize some control-sequences

```

434   \global\let\\=\@oldcr
435   \global\let\@table@first@head\undefined
436   %% \global\let\@table@last@tail\undefined
437   \global\let\@process@tablecaption\relax

```

Extension: For the extension, write the number of the last page to the `.aux` file. Also, if we are in the `iso` class, reset the 'float' flag.

```

438   \PWSToplastpagenum
439   \infloatfalse}

```

`\PWSToplastpagenum` *Extension:* This routine is responsible for writing the number of the last page of the supertabular to the `.aux` file.

What gets written is `\PWST@vi{4}`, assuming that the value of `c@PWSTtable` is 6 and the value of `PWSTcurpage` is 4.

```

440 \newcommand{\PWSToplastpagenum}{%

```


There are a number of cases to consider. The first decision is whether the current page is the previously calculated last page.

```
441 \ifnum\PWSTcurpage=\PWSTlastpage
```

The current table ends on the calculated last page. There are four cases to consider:

1. The table has not overflowed (`firstcall` is TRUE) and the table is not empty — this page is still the last page.
2. The table has not overflowed (`firstcall` is TRUE) and the table is empty — this page is after the actual last page, so decrease the page number.
3. The table has overflowed (`firstcall` is FALSE) and the overflow is large enough to generate a non-empty table on the next page — increment the page number.
4. The table has overflowed (`firstcall` is FALSE) and the overflow is small enough to generate an empty table on the next page — this page is still the last page.

```
442 \iffirstcall % on last, no overflow
443 %% \ifnum\PWSTlines < \PWSTlasthead % this table is empty
444 \ifnum\PWSTlines < \@ne % this table is empty
445 \global\advance\PWSTcurpage \m@ne
446 \fi
447 \else % overflow
448 %% \ifnum\PWSTlines > \tw@ % enough for another page
449 \ifnum\PWSTlines > \z@ % enough for another page
450 \global\advance\PWSTcurpage \@ne
451 \fi
452 \fi
453 \else
```

The table has ended on a page that is not the calculated last page. If the table is empty, then decrement the page number, else this is the last page.

```
454 %% \ifnum\PWSTlines < \PWSThead % empty table
455 \ifnum\PWSTlines < \@ne % empty table
456 \global\advance\PWSTcurpage \m@ne
457 \fi
458 \fi
```

Finally, write out the ‘new’ last page number.

```
459 \if@files\immediate\write\@auxout%
460 {\gdef\string\PWST@romannumeral@c@PWSTtable{\the\PWSTcurpage}}%
461 \ST@trace\tw@{Table \the\c@PWSTtable:\MessageBreak
462 wrote \the\PWSTcurpage\space as the last page}%
463 \fi}
464
```

```

\endmpxtabular These close the mpxtabular and mpxtabular* environments.
\endmpxtabular* 465 \def\endmpxtabular{%
466 \ifx\@table@last@tail\undefined
467 \@tabletail
468 \else
469 \@table@last@tail
470 \fi
471 \csname endtabular\ifST@star*\fi\endcsname
472 \endminipage
Now call the common code for all \end....
473 \x@endsupertabular
Finish per the original code.
474 \ST@trace\tw@{Ended an mpxtabular\ifST@star*\fi}}
The definition of the ending of the mpxtabular* environment is simple:
475 \expandafter\let\csname endmpxtabular*\endcsname\endmpxtabular

\ST@restore This macro restores the original definitions of the macros that handle parbox
entries and the ‘end of row’ macros.
476 \def\ST@restore{%
477 \ifx\undefined\@classix
478 \let\@tabularcr\org@tabularcr
479 \else
480 \let\@arraycr\org@tabularcr
481 \fi
482 \let\@startpbox\org@startpbox
483 \let\@endpbox\org@endpbox}

\inner@tabular In order to facilitate complete tabular environments to be in a cell of a
\inner@tabular* supertabular we need to adapt the definition of the original environments. For
the inner tabular a number of definitions have to be restored.
484 \def\inner@tabular{%
485 \ST@restore
486 \let\@=\@oldcr
487 \noindent
488 \org@tabular}
489 \@namedef{inner@tabular*}{%
490 \ST@restore
491 \let\@=\@oldcr
492 \noindent
493 \csname org@tabular*\endcsname}

\ST@cr This macro is called by each \@ inside the tabular environment. It updates the
estimate of the amount of space left on the current page and starts a new page if
necessary.
494 \def\ST@cr{%
495 \noalign{%
496 \ST@trace\thr@{Parbox height: \the\ST@pboxht\MessageBreak

```

```

497             Line height: \the\ST@lineht}%
498     \ifnum\ST@pboxht<\ST@lineht

```

If there is a non-empty line, but an empty parbox, then `\ST@pboxht` might be non-zero, but too small thereby breaking the algorithm. Therefore we estimate the height of the line to be `\ST@lineht` in this case, and store it in `\ST@prevht`.

```

499     \global\advance\ST@pageleft -\ST@lineht
500     \global\ST@prevht\ST@lineht
501     \else

```

When the parbox is not empty we take its height into account plus a little extra.

```

502     \global\advance\ST@pboxht \PWST@xentrystretch\ST@pboxht
503     \global\advance\ST@pboxht \ST@stretchht
504     \ST@trace\thr@@{Added par box with height \the\ST@pboxht}%
505     \global\advance\ST@pageleft -\ST@pboxht
506     \global\ST@prevht\ST@pboxht
507     \global\ST@pboxht\z@
508     \fi

```

`\ST@toadd` is the value of the optional argument of `\`.

```

509     \global\advance\ST@pageleft -\ST@toadd
510     \global\ST@toadd=\z@
511     \ST@trace\thr@@{Space left for xtabular: \the\ST@pageleft}%

```

Extension: Increment the line number at this point.

```

512     \global\advance\PWSTlines \@ne
513     \ST@trace\thr@@{Line counter incremented by one to: \the\PWSTlines}%
514 }% end of noalign

```

In general, when the `\ST@pageleft` has become negative, the last row was so high that the supertabular doesn't fit on the current page. In this case we skip the current page and start at the top of the next one; otherwise `TEX` will move this part of the table to a new page anyway, probably with a message about an overfull `\vbox`.

Extension: For the extension I do some special handling if we are on the last page. Essentially the idea is not to start a new page, but to continue on the current page, noting any overflow.

```

515 \ifnum\PWSTcurpage=\PWSTlastpage
516     \PWST@lastpagecr
517 \else

```

Execute the original code.

```

518     \ifnum\ST@pageleft<\z@
519         \ST@skippage
520     \else

```

When there is not enough space left on the current page, we start a new page. To compute the amount of space needed we use the height of the previous line (`\ST@prevht`) as an estimate of the height of the next line. If we are processing an `mpsupertabular` we also need to take the height of the footnotes into account.

```

521     \noalign{\global\@tempdima\ST@tailht

```

```

522     \global\advance\@tempdima\ST@prevht
523   \ifST@mp
524     \ifvoid\@mpfootins\else
525       \global\advance\@tempdima\ht\@mpfootins
526       \global\advance\@tempdima 3pt
527     \fi
528   \fi}% end noalign
529   \ifnum\ST@pageleft<\@tempdima
530     \ST@newpage
531   \else

```

This line is necessary because the tablehead has to be inserted *after* the `\if\else\fi`-clause. For this purpose `\ST@next` is used. In the middle of tableprocessing it should be an *empty* macro (*not* `\relax`).

```

532     \noalign{\global\let\ST@next\@empty}%
533   \fi
534 \fi

```

Extension: Close off the `\iflastpage`;

```
535 \fi
```

and finish per the original code.

```

536 \ST@next}
537

```

`\PWST@lastpagecr` *Extension:* This routine handles newlines on the last page of a supertabular. The idea is that when we are on the last page the table continues to be processed until the end without calling for a newpage even if the table will be too long. I do need to record whether or not the table has ‘overflowed’ the allowable space on the page. The code is very similar to the last part of the code for `\ST@cr`.

```

538 \newcommand{\PWST@lastpagecr}{%
539 \noalign{%
540   \ifnum\ST@pageleft<\z@

```

The table has overflowed, so record the fact.

```

541     \PWST@setfirstcall
542   \fi

```

Now continue along the lines of `\ST@cr`.

```

543   \global\@tempdima\ST@tailht
544   \global\advance\@tempdima\ST@prevht
545   \ifST@mp
546     \ifvoid\@mpfootins\else
547       \global\advance\@tempdima\ht\@mpfootins
548       \global\advance\@tempdima 3pt
549     \fi
550   \fi
551   \ifnum\ST@pageleft<\@tempdima

```

Again, the table has overflowed.

```

552     \PWST@setfirstcall
553   \fi

```

Finish like `\ST@cr`.

```
554     \global\let\ST@next\@empty
555     }}
```

`\PWST@setfirstcall` *Extension:* This routine records that a table on the last page has overflowed by setting `firstcall` to FALSE. If it is the first such overflow it also zeroes the line counter.

```
556 \newcommand{\PWST@setfirstcall}{%
557   \iffirstcall
558   \global\firstcallfalse
559   \global\PWSTlines=\z@
560   \ST@trace\thr@@{Overflow on last page. Line counter set to \the\PWSTlines}%
561   \fi}
```

`\ST@skipfirstpart` This macro skips the current page and moves the entire supertabular that has been built so far to the next page.

```
562 \def\ST@skipfirstpart{%
563   \noalign{%
564     \ST@trace\tw@{Tabular too high, moving to next page}%
```

In order for this to work properly we need to adapt the value of `\ST@pageleft`. When this macro is called it has a negative value. We should add the height of the next page to that (`\@colroom`). From the result the ‘normal’ height of the supertabular should be subtracted (`\@colroom - \pagetotal`). This could be coded as follows:

```
    \ST@dimen\@colroom
    \advance\ST@dimen-\pagetotal
    \global\advance\ST@pageleft\@colroom
    \global\advance\ST@pageleft-\ST@dimen
```

However, note that `\@colroom` is added *and* subtracted. Thus the code can be simplified to:

```
565   \global\advance\ST@pageleft\pagetotal
```

Then we can set `\ST@pagesofar` to zero and start the new page.

```
566   \global\ST@pagesofar\z@
567   \newpage
```

Finally we make sure that this macro can only be executed once for each supertabular by changing the definition of `\ST@skippage`.

```
568   \global\let\ST@skippage\ST@newpage
569   }}
```

`\ST@newpage` This macro performs the actions necessary to start a new page.
This macro is also modified for the extension to supertabular.

```
570 \def\ST@newpage{%
571   \noalign{\ST@trace\tw@{Starting new page, writing tail}}%
```

Output `\tabletail`, close the tabular environment, close a minipage if necessary, output all material and start a fresh new page.

```
572 \@tabletail
573 \ifST@star
574   \csname endtabular*\endcsname
575 \else
576   \endtabular
577 \fi
578 \ifST@mp
579   \endminipage
580 \fi
```

Then we make sure that `\ST@skippage` can no longer be executed for this supertabular by changing its definition.

```
581 \global\let\ST@skippage\ST@newpage
```

On with the output.

Extension: The original code had the next line as `\newpage\@calnextpageht`. However, if the general header has a vertical height that differs from the first header, then the table on the continuation pages may run short or, more disconcerting, long. The extension, I think, cures that by using a different algorithm to calculate the height on the next page.

```
582 \newpage\PWSTcalnextpageht
583 \ST@trace\tw@{writing head}%
```

Extension: The original code just let `\ST@next` to `\@tablehead`. The extension has to handle the special case of of the heading on the last page.

```
584 \PWSTsethead
```

Now we are back to the original supertabular code.

```
585 \ifST@mp
586   \noindent\minipage{\columnwidth}%
587   \parfillskip\ST@parfillskip
588   \rightskip \ST@rightskip
589   \leftskip \ST@leftskip
590 \fi
591 \noindent
592 \ifST@star
593   \expandafter\csname org@tabular*\expandafter\endcsname
594   \expandafter{\expandafter\ST@wd\expandafter}%
595   \expandafter{\ST@tableformat}%
596 \else
597   \expandafter\org@tabular\expandafter{\ST@tableformat}%
598 \fi}
```

`\PWSTsethead` *Extension:* This is more extension code for use within `\ST@newpage`. It provides the proper table head for the page about to be processed.

```
599 \newcommand{\PWSTsethead}{%
```

First the line counter is zeroed.

```

600 \global\PWSTlines=\z@
601 \ST@trace\thr@{\Newpage, line counter set to: \the\PWSTlines}%
    The current page counter is incremented and it is checked against the old page
    counter to see if this is the last page of this supertabular.
602 \global\advance\PWSTcurpage\@ne
603 \ST@trace\tw@{Table \the\c@PWSTtable:\MessageBreak
604             current page = \the\PWSTcurpage,\MessageBreak
605             last page = \the\PWSTlastpage}%
606 \ifnum\PWSTcurpage=\PWSTlastpage
607   \ST@trace\tw@{Newpage is the last page}%
    We are on the last page. If there are more than one pages and the last table heading
    has been specified, then the heading is set to \@table@last@head, otherwise it is
    set to \@tablehead.
608   \ifnum\PWSTcurpage>\@ne
609     \ifx\@table@last@head\relax
610       \let\ST@next\@tablehead
611       \ST@trace\tw@{Set heading to tablehead}%
612     \else
613       \let\ST@next\@table@last@head
614       \ST@trace\tw@{Set heading to tablelasthead}%
615     \fi
616   \fi
617 \else
    We are not on the last page, so just set the heading to \@tablehead.
618   \let\ST@next\@tablehead
619   \ST@trace\tw@{Set heading to tablehead}%
620 \fi}
    The end of this package
621 \</xtab>

```

References

- [GMS94] Michel Goossens, Frank Mittelbach, and Alexander Samarin. *The LaTeX Companion*. Addison-Wesley Publishing Company, 1994.
- [Wil96] Peter R. Wilson. *LaTeX for standards: The LaTeX package files user manual*. NIST Report NISTIR, June 1996.

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

Symbols	<code>\@startpbox</code>	325	<code>\@tablehead</code> . .	220,
<code>\@endpbox</code>		326		

226, 336, 338, 378, 394, 413, 436	\@arraycr . 328, 329, 503	\@arrayparboxrestore . 140, 141, 144, 145, 223, 233, 270, 276, 283, 289	\@arstrutbox 129, 147, 156	\@auxout 481	\@calfirstpageheight 261	\@calfirstpageht 175, 342	\@calnextpageht 188, 203, 213, 263	\@classix 320, 500	\@colroom 178, 193, 258, 265, 304	\@dblarg 16	\@depth 130	\@endpbox 324, 331, 333, 506	\@finalstrut . . 147, 156	\@height 130	\@ifnextchar . . 116, 369, 381, 397, 416	\@ifstar 114	\@ifundefined 29	\@initisotab 29, 34	\@makecaption 42	\@mpfootins 549, 550, 571, 572	\@mpsupertabular 397–399	\@namedef 380, 384, 415, 419, 513	\@nameuse 381, 382, 416, 417	\@oldcr 318, 455, 510, 515	\@parboxrestore . . . 39	\@process@tablecaption 19, 20, 317, 344, 452, 458	\@savcr . . 51, 54, 78, 81	\@spaces 90	\@startpbox 323, 330, 332, 505	\@supertabular 369, 370, 371	\@table@first@head . . 56, 335, 338, 456	\@table@last@head . . 71, 279, 638, 642	\@table@last@tail . . . 83, 273, 439, 442, 457, 488, 491	\@tablehead 49, 292, 336, 639, 647	\@tabletail 76, 230, 236, 286, 440, 489, 600	\@tabularcr 321, 322, 501	\@topcaptionfalse . 11	\@topcaptiontrue 9, 10, 453	\@width 130	\@xtablecaption . . . 15	\table@first@head 354, 391, 433, 444, 447, 493, 497, 517, 602, 621	\endminipage . . 494, 607	\endmpxtabular 487	\endmpxtabular* . . . 487	\endtabular 226, 236, 273, 279, 286, 292, 604	\endxtabular 438	\endxtabular* 438	\estimate@lineht 165, 341	F	\firstcallfalse . . . 584	\firstcalltrue 365	G	\GenericWarning . . . 90	H	\ht 148, 157, 227, 237, 247, 274, 280, 287, 293, 550, 572	I	\if@filesw 481	\if@firstcolumn . . . 183	\if@topcaption 9, 41, 43, 245, 317, 344, 450	\if@twocolumn 181	\iffirstcall 66, 464, 583	\ifinfloat 31	\ifST@mp 23, 548, 570, 606, 613	\ifST@star 22, 444, 446, 493, 496, 601, 620	\ifvoid 549, 571	\ignorespaces . . . 37, 42	\immediate 481	\infloatfalse 460	\infloattrue 366	\inner@tabular 311, 508	\inner@tabular* . . . 508	L	\leftskip 405, 411, 426, 432, 617
--------------------------------------	---------------------------	--	---	------------------------	---------------------------------------	--	---	----------------------------	--	-----------------------	-----------------------	---	---------------------------	------------------------	---	------------------------	----------------------------	-----------------------------	----------------------------	---	---	--	---	----------------------------	--------------------------	---	----------------------------	-----------------------	---	---	---	--	--	---	--	---------------------------	------------------------	--	-----------------------	--------------------------	--	---------------------------	----------------------------	---------------------------	---	----------------------------	---------------------------	--	----------	---------------------------	----------------------------	----------	--------------------------	----------	---	----------	--------------------------	---------------------------	--	---------------------------	---------------------------	-------------------------	--	---	----------------------------	----------------------------	--------------------------	---------------------------	----------------------------	-------------------------	---------------------------	----------	--

M		
<code>\MessageBreak</code>	<code>\PWSTcalchtlines</code> ..	<code>\ST@lineht</code>
. . . . 170, 179, <u>269</u> , 363	. <u>105</u> , 166–168,
483, 521, 632, 633	<code>\PWSTcalnextpageht</code> .	170, 172, 173,
<code>\minipage</code> . 408, 429, 614 <u>296</u> , 610	239, 243, 522–525
<code>\mpxtabular</code> <u>396</u>	<code>\PWSTcapht</code>	<code>\ST@mpfalse</code> . . . 375, 389
<code>\mpxtabular*</code> <u>415</u>	<u>13</u> , 45, 247, 248,	<code>\ST@mptrue</code> . . . 403, 424
	250, 252, 253, 259	<code>\ST@newpage</code> 555, 595, <u>598</u>
	<code>\PWSTcurpage</code> . . . <u>58</u> ,	<code>\ST@next</code> . . 557, 561,
	297, 362, 463,	579, 639, 642, 647
	467, 472, 478,	<code>\ST@pageleft</code> . 45, 46,
	482, 484, 540,	<u>93</u> , 95, 97, 178,
	631, 633, 635, 637	180, 185–187,
	<code>\PWSThead</code> <u>58</u> , 476	192, 193, 196,
	<code>\PWSTinit</code> 343, <u>351</u>	201, 205, 211,
	<code>\PWSTlasthead</code> . . <u>58</u> , 465	215, 219, 241,
	<code>\PWSTlastpage</code> . . <u>58</u> ,	255, 258, 259,
	357, 359, 361,	265, 267, 304,
	463, 540, 634, 635	305, 307, 346–
	<code>\PWSTlines</code> <u>58</u> ,	349, 524, 530,
	364, 465, 466,	534, 536, 543,
	470, 471, 476,	554, 565, 576, 592
	477, 537, 538,	<code>\ST@pagesofar</code> . <u>103</u> ,
	585, 586, 629, 630	177, 185, 187,
	<code>\PWSToplastpagenum</code> .	192, 196, 197,
 459, <u>462</u>	201, 205, 206,
	<code>\PWSTpenultimate</code> <u>58</u> , 297	211, 215, 216,
	<code>\PWSTsethead</code> . . 612, <u>628</u>	260, 266, 306, 593
	<code>\PWSTtempc</code>	<code>\ST@parfillskip</code> . . .
	. <u>58</u> , 353, 355, 359 <u>25</u> , 406,
		409, 427, 430, 615
		<code>\ST@pbox</code> <u>110</u> ,
		140, 141, 144,
		145, 148, 149,
		154, 157, 158, 163
		<code>\ST@pboxht</code> <u>104</u> , 150,
		151, 159, 160,
		521, 523, 527–532
		<code>\ST@prevht</code> . . . <u>105</u> ,
		525, 531, 547, 569
		<code>\ST@restore</code>
		. 224, 234, 271,
		277, 284, 290,
		449, <u>499</u> , 509, 514
		<code>\ST@rightskip</code> <u>25</u> , 404,
		410, 425, 431, 616
		<code>\ST@skipfirstpart</code> .
	 340, <u>589</u>
		<code>\ST@skippage</code>
		. 340, 544, 595, 609
		<code>\ST@starfalse</code> . 374, 402
N		
<code>\newbox</code> 110		
<code>\newcount</code> 2, 59–65		
<code>\newif</code> . 9, 22, 23, 31, 66		
<code>\newskip</code> 25–27		
<code>\noalign</code> . 50, 54, 77,		
81, 95, 97, 131,		
134, 520, 546,		
557, 564, 590, 599		
<code>\normalsize</code> 40		
<code>\notablelasthead</code> . . <u>71</u>		
O		
<code>\org@endpbox</code>		
. . . . 324, 331, 506		
<code>\org@startpbox</code>		
. . . . 323, 330, 505		
<code>\org@tabular</code> . . 310,		
377, 412, 512, 625		
<code>\org@tabularcr</code> 52, 79,		
321, 328, 501, 503		
P		
<code>\pagetotal</code> 177, 179, 592		
<code>\PWST@</code> 482		
<code>\PWST@generalht</code> . . .		
. <u>67</u> , 288, 294, 302		
<code>\PWST@ht</code> . . . <u>67</u> , 274,		
275, 280, 281,		
287, 288, 293,		
294, 299, 302, 305		
<code>\PWST@lastht</code> . . . <u>67</u> ,		
275, 281, 282, 299		
<code>\PWST@lastpagecr</code> . .		
. 541, <u>563</u>		
<code>\PWST@setfirstcall</code> .		
. . . . 566, 577, <u>582</u>		
<code>\PWST@thecaption</code> . .		
. <u>13</u> , 18, 246		
<code>\PWST@xentrystretch</code>		
. <u>98</u> , 172, 527		
R		
<code>\romannumeral</code> . 354, 482		
S		
<code>\setSTheight</code> <u>94</u>		
<code>\shrinkheight</code> <u>6</u> , <u>94</u>		
<code>\ST@aendpbox</code> . . <u>146</u> , 333		
<code>\ST@argtabularcr</code> . . <u>112</u>		
<code>\ST@astartpbox</code> <u>142</u> , 332		
<code>\ST@caption</code> 19, <u>33</u>		
<code>\ST@cr</code> 118, 131, 137, <u>519</u>		
<code>\ST@dimen</code>		
. <u>109</u> , 148–151,		
153, 157–160, 162		
<code>\ST@endpbox</code> . . . <u>146</u> , 326		
<code>\ST@headht</code> <u>101</u> , 221,		
227, 229, 242, 346		
<code>\ST@leftskip</code> <u>25</u> , 405,		
411, 426, 432, 617		

<code>\ST@startpbox</code>	. 139 , 325	347, 349, 356,	285, 291, 310, 311
<code>\ST@starttrue</code>	.. 388 , 423	361, 373, 385,	<code>\thr@@</code> .. 5 , 521 , 529 ,
<code>\ST@stretchht</code>	. 105 ,	401, 420, 446,	536 , 538 , 586 , 630
	168 , 169 , 171 , 528	483, 496, 521,	<code>\topcaption</code> 9
<code>\ST@tableformat</code>	...	529, 536, 538,	
	. 225 , 235 , 272 ,	586, 591, 599,	U
	278 , 285 , 291 ,	611, 630, 632,	<code>\unskip</code> 123
	372 , 377 , 386 ,	636, 640, 643, 648	<code>\unvbox</code> 163
	393 , 400 , 412 ,	<code>\ST@wd</code> 24 , 387 ,	
	421 , 435 , 623 , 625	392 , 422 , 434 , 622	V
<code>\ST@tabularcr</code>	<code>\ST@xargarraycr</code> 123 , 127	<code>\vbox</code> . 223 , 233 , 246 ,
 112 , 322 , 329	<code>\ST@xtabularcr</code> 112	270 , 276 , 283 , 289
<code>\ST@tailht</code>	101 , 231 ,	<code>\ST@yargarraycr</code> 125 , 127	<code>\vrule</code> 130
	237 , 239 , 240 ,	<code>\string</code> 482	<code>\vtop</code> . 140 , 141 , 144 , 145
	244 , 348 , 546 , 568	<code>\straceoff</code> 86	
<code>\ST@toadd</code>	. 108 , 131 ,	<code>\straceon</code> 86	W
	135 , 136 , 534 , 535		<code>\write</code> 481
<code>\ST@trace</code>	46 , 88 , 170 ,	T	
	173 , 176 , 179 ,	<code>\tablecaption</code> 10 , 11 , 15	X
	182 , 184 , 189 ,	<code>\tablefirsthead</code> ... 48	<code>\x@endsupertabular</code> .
	191 , 200 , 202 ,	<code>\tablehead</code> 48 445 , 448 , 495
	210 , 212 , 219 ,	<code>\tablelasthead</code> 71	<code>\x@supertabular</code> 309 ,
	229 , 240 , 241 ,	<code>\tablelasttail</code> 75	376 , 390 , 407 , 428
	252 , 254 , 256 ,	<code>\tabletail</code> 75	<code>\xentrystretch</code> ... 6 , 98
	264 , 267 , 282 ,	<code>\tabular</code> 225 ,	<code>\xtabular</code> 368
	298 , 301 , 307 ,	235 , 272 , 278 ,	<code>\xtabular*</code> 380